

GASKET COMPOSIT

IS A PART OF THE FLEXIBLE SLURRY HOSE SYSTEM COMPOSIT. IT IS DESIGNED FOR THE USE AS A SEALING ELEMENT WHEN CONNECTING SEGMENTS OF THE HOSE SYSTEM COMPOSIT



BASIC DIMENSIONS OF THE GASKET COMPOSIT

Part No	Inner diameter of the hose		Inner diameter of the gasket		Outer diameter of the gasket		Height of the gasket		Weight of the gasket	
	mm	inch	mm	inch	mm	inch	mm	inch	kg	pound
G050	50	1 7/8	43	1 5/7	92	3 5/8	19	3/4	0.08	0.2
G065	65	2 1/2	59	2 1/3	110	4 1/3	19	3/4	0.14	0.3
G076	76	2 7/8	70	2 3/4	125	4 8/9	20	7/9	0.16	0.4
G102	102	3 7/8	95	3 3/4	150	5 8/9	19	3/4	0.17	0.4
G114	114	4 1/2	108	4 1/4	170	6 5/7	24	1	0.38	0.8
G133	133	5 1/4	120	4 5/7	187	7 3/8	25	1	0.42	0.9
G152	152	5 7/8	146	5 3/4	205	8 1/9	25	1	0.67	1.5
G159	159	6 1/4	142	5 3/5	203	8	29.5	1 1/6	0.7	1.5
G170	170	6 5/8	163	6 3/7	225	8 6/7	25	1	0.38	0.8
G200	200	7 7/8	196	7 5/7	255	10	25	1	0.42	0.9
G219	219	8 5/8	212	8 1/3	280	11	26	1	0.8	1.8
G245	245	9 5/8	237	9 1/3	300	11 4/5	25	1	0.8	1.8
G273	273	10 5/8	267	10 1/2	325	12 4/5	25	1	0.89	2.0
G300	300	11 7/8	287	11 2/7	354	13 8/9	25	1	0.95	2.1
G325	325	12 5/8	313	12 1/3	389	15 1/3	26	1	1.15	2.5
G351	351	13 5/8	338	13 2/7	415	16 1/3	25	1	1.21	2.7
G377	377	14 7/8	370	14 4/7	440	17 1/3	26	1	1.5	3.3
G402	402	15 5/8	389	15 1/3	471	18 5/9	26	1	1.6	3.5
G426	426	16 5/8	417	16 3/7	500	19 2/3	26	1	1.8	4.0
G508	508	19 7/8	499	19 5/8	590	23 2/9	30	1 1/6	2.2	4.9
G530	530	20 5/8	522	20 5/9	610	24	29	1 1/7	3.04	6.7
G610	610	23 5/7	602	23 5/7	680	26 7/9	29	1 1/7	3.3	7.3

DESCRIPTION

Gaskets COMPOSIT are designed for application with the flexible slurry hoses COMPOSIT. The consolidation provides a sealing connection without any reduction of the internal diameter of the line.

Structurally the gasket COMPOSIT constitutes of a rubberized steel ring.

INSTALLATION

Installation is executed conjointly with installation of couplings.